

# Armstrong™

## LUSTER 24

An extremely durable, high solids, buffable and burnishable floor finish. LUSTER 24 will stand up to heavy traffic and wear, survive repeated detergent washing and still provide outstanding gloss. It is economical with respect to the fact that LUSTER 24 requires fewer coats than regular finishes. It can be used on all floors including floors made of vinyl, vinyl asbestos, asphalt tile, linoleum, linotile, rubber, terrazzo. (It is not recommended, however, for unsealed wood.) LUSTER 24 is very practical for use where large areas must be finished, such as supermarkets, shopping malls and hospitals.

### Use/Benefits

High solids content.  
For heavily trafficked floors and outstanding gloss.  
Harder, tougher finish.  
Highly resistant to detergent scrubbing, black marks and scuffing.  
Economical; sealing usually not necessary which reduces labour costs.

### Physical Properties

Appearance	-	White liquid emulsion
Odour	-	Acrylic
pH	-	8.0 - 9.0
Total Solids	-	24%
Coverage	-	2000-2500 sq. ft. per gallon

### Recommendations

Floors must be properly prepared before application of finish. Strip old finish using one of our ami Strippers. Rinse well and neutralize. Rinse again to eliminate odour. Apply two thin, even coats of finish using a fresh, clean string mop. Allow 45-60 minutes between coats. Do not scrub or damp-mop for at least 48 hours after final application.

To maintain: Avoid the use of high alkaline products such as strippers. Do not use powdered cleaners. For regular maintenance use our Neutral Clean neutral pH cleaner. Damp mop before spray buffing. Apply additional coats of finish as required to maintain appearance.

### Codes

4 x 4 Litre/case .....	42270
20 Litre pail.....	42271
205 Litre drum .....	42272

**M.S.D.S. #0118 Available upon Request**

11/01/05