

# Armstrong™

## SPLENDOR SF

Splendor SF is a durable high gloss sealer finish effective in high traffic areas. Can be machine buffed or burnished for a wet look result or just mopped on. Suitable for use on asphalt tile, linoleum, linotile, rubber, asphalt, terrazzo, vinyl and vinyl asbestos.

### Use/Benefits

Durable  
Fast Drying  
Versatile  
Suitable on many types of floors  
Low odour

### Physical Properties

Appearance - Milky emulsion  
Odour - Slight ammonia odour  
pH - 8.5 – 9.5  
Specific Gravity - 1.032

### Recommendations

Floor must be properly prepared before application of finish. Strip old finish using a stripper. Rinse well and neutralize. If vinegar is employed in neutralizing, use sparingly and rinse again to eliminate odour. Apply two thin even coats of finish using a fresh clean string mop. Allow 45 – 60 minutes between coats. Do not scrub or damp-mop for at least 48 hours after final application.

Maintenance: Avoid use of highly alkaline products (high pH), such as strippers. Do not use powdered cleaners. For regular maintenance, use a neutral pH cleaner. Damp-mop before spray-buffing. Apply additional coats of finish as required to maintain appearance.

### Codes

4x4 Litres/case ..... 42160  
20 Litre pail ..... 42161

**M.S.D.S. #0072 Available upon Request**

01/26/06