

Armstrong™

LUSTER 18

A premium-grade semi-buffable, polymer floor finish for use on all types of flooring, except unsealed wood. LUSTER 18 is recommended for use on asphalt tile, linoleum, linotile, rubber, asphalt, terrazzo, vinyl, vinyl asbestos. LUSTER 18 has superior durability characteristics, is able to resist scuffs and black marks. It has been formulated to feature a high gloss and able to withstand heavy traffic as well as detergent scrubbing and much more abuse. It is easily applied and may be damp mopped repeatedly without harming the appearance.

Use/Benefits

- Polymer-acrylic.
- Non-yellowing.
- Mop or machine scrubable.
- Will not harm the finish.
- Easy application - Time saving - Reduces maintenance costs.
- Resists scuffs and black marks.
- Can be used on almost any floor.
- Fewer products needed for magnificent-looking floors.

Physical Properties

Appearance	-	White opaque liquid emulsion
Odour	-	Acrylic
pH	-	8.0-9.0
Total Solids	-	18%
Coverage	-	2000-2500 sq. ft. per gallon

Recommendations

Floors must be properly prepared before application of finish. Strip old finish using one of our AMI Strippers. Rinse well and neutralize. Rinse again to eliminate odour. Apply two thin, even coats of finish using a fresh, clean string mop. Allow 45-60 minutes between coats. Do not scrub or damp-mop for at least 48 hours after final application.

To maintain: Avoid the use of high alkaline products such as strippers. Do not use powdered cleaners. For regular maintenance use our Neutral Clean neutral pH cleaner. Damp mop before spray buffing. Apply additional coats of finish as required to maintain appearance.

Codes

4 x 4 Litre/case	42265
20 Litre pail.....	42266
205 Litre drum	42267

M.S.D.S. #0116 Available upon Request